



New Modular Flood Light

Main features:

1. **IP66**, integrated die-casting aluminum mould
2. Patent certification, modular design - easy maintenance;
3. Model connectable, high power solutions Max 960W
4. Flat honeycomb heat sink - good heat dissipation;
5. High Luminous Efficiency: **120-150 lm/W**;
6. Certificates: **CE, RoHS, CB ,GS**;

Pictures



Item No.	Dimension	Voltage	Power	Color Temp.	Light Source	LED Quantity	Luminous Flux	Driver	Beam Angle	IP Level	Lifespan
120lm/w											
SL-S1-50BA1	346*200*65mm	AC90-305V	50W	Warm white: 2800-3500K Natural white: 3800~4500K Pure white: 5500~6500K	Philips Lumileds 3030	48 pcs	6,000lm	MeanWell ELG Driver	30°/60°/90°/ 80°140°	IP66	>50,000H
SL-S1-100BA1	365*310*60mm	AC180-305V	100W			96 pcs	12,000lm				
SL-S1-150BA1	365*365*60mm		150W			144 pcs	18,000lm				
SL-S1-200BA1	420*365*60mm		200W			192 pcs	24,000lm				
SL-S1-240BA1	420*365*60mm		240W			192 pcs	28,800lm				
SL-S1-300BA1	590*387*63mm		AC100-240V			300W	288pcs	36,000lm			
SL-S1-400BA1	695*435*65mm	AC180-305V	400W			384 pcs	48,000lm	MeanWell ELG Driver			
SL-S1-480BA1	695*435*65mm		480W			384 pcs	57,600lm				
SL-S1-600BA1	695*730*65mm		600W			576 pcs	72,000lm				
SL-S1-960BA1	711*775*352mm		960W			768pcs	115,200lm				

150lm/w											
SL-S1-50BB1	346*200*65mm	AC90-305V	50W	Warm white: 2800-3500K Natural white: 3800~4500K Pure white: 5500~6500K	Philips Lumileds 5050	48 pcs	7,500lm	MeanWell ELG Driver	30°/60°/90°/ 80°140°	IP66	>50,000H
SL-S1-100BB1	365*310*60mm	AC180-305V	100W			96 pcs	15,000lm				
SL-S1-150BB1	365*365*60mm		150W			144 pcs	22,500lm				
SL-S1-200BB1	420*365*60mm		200W			192 pcs	30,000lm				
SL-S1-240BB1	420*365*60mm		240W			192 pcs	36,000lm				
SL-S1-300BB1	590*387*63mm		AC100-240V			300W	288pcs	45,000lm			
SL-S1-400BB1	695*435*65mm	AC180-305V	400W			384 pcs	60,000lm	MeanWell ELG Driver			
SL-S1-480BB1	695*435*65mm		480W			384 pcs	72,000lm				
SL-S1-600BB1	695*730*65mm		600W			576 pcs	90,000lm				
SL-S1-960BB1	711*775*352mm		960W			768pcs	144,000lm				