





IP68 LED Fountain Light			
Model	Picture	Description	Color
SL-SDD-500003		Voltage: DC12V Power: 3*1W Specification: 82MM Material: Stainless steel + Tempered glass All RGB color is AC24V	red
			yellow
			blue
			green
			white
			warm white
			rgb
SL-SDD-500006		Voltage: DC24V Power: 6*1W Specification: :Φ120mm Material:: Stainless steel + Tempered glass All RGB color is AC24V	red
			yellow
			blue
			green
			white
			warm white
			rgb
SL-SDD-500009		Voltage: DC24V Power: 9*1W Specification:: Φ145mm Material: Stainless steel + Tempered glass All RGB color is AC24V	red
			yellow
			blue
			green
			white
			warm white
			rgb
SL-SDD-500012		Vlotage: DC24V Power: 12*1W Specification: Φ160mm Material: Stainless steel + Tempered glass All RGB color is AC24V	red
			yellow
			blue
			green
			white
			warm white
			rgb
SL-SDD-500015		Vlotage: DC24V Power: 15*1W Specification:: Φ175mm Material: Stainless steel + Tempered glass All RGB color is AC24V	red
			yellow
			blue
			green
			white
			warm white
			rgb
SL-SDD-50006		Voltage: DC24V Power: 6*1W Chip:Epistar Diammter: D130mm*H85mm Lumen:100lm/w CRI:85 Power factor: 0.9 Beam angle: 60 degree Material: Stainless steel + Glass All RGB color is AC24V	red
			yellow
			blue
			green
			white
			warm white
			rgb

Model	Picture	Description	Color
SL-SDD-50009		<p>Voltage: DC24V Power: 9*1W Chip:Epistar Diammter: D160mm*H85mm Lumen: 100lm/w CRI:85 Power factor: 0.9 Beam angle: 60 degree Material: Stainless steel + Glass All RGB color is AC24V</p>	red
			yellow
			blue
			green
			white
			warm white
			rgb
SL-SDD-500012		<p>Voltage: DC24V Power: 12*1W Chip:Epistar Diammter: D180mm*H85mm Lumen: 100lm/w CRI:85 Power factor: 0.9 Beam angle: 60 degree Material: Stainless steel + Glass All RGB color is AC24V</p>	red
			yellow
			blue
			green
			white
			warm white
			rgb
SL-SDD-500018		<p>Voltage: DC24V Power: 18*1W Chip:Epistar Diammter: D200mm*H85mm Lumen: 100lm/w CRI:85 Power factor: 0.9 Beam angle: 60 degree Material: Stainless steel + Glass All RGB color is AC24V</p>	red
			yellow
			blue
			green
			white
			warm white
			rgb
SL-SDD-500024		<p>Voltage: DC24V Power: 24*1W Chip:Epistar Diammter: D200mm*H85mm Lumen: 100lm/w CRI:85 Power factor: 0.9 Beam angle: 60 degree Material: stainless steel + glass All RGB color is AC24V</p>	red
			yellow
			blue
			green
			white
			warm white
			rgb