







LED Aluminium / Stainless Steel #304 Inground Light

Picture	Item	Power (W)	Description	Input V	Color Temp.	LED Chips	CRI (Ra)	Beam angle	Dimension D*H(mm)	Driver	Light Colour	Material	IP Grade
	SLGD-BDMD-001 DMX512 external control	1W	32mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ32*65 Hole size: Φ28	Constant current driver	White / Y.B.G.R	Aluminum	IP68
	SLGD-BDMD-003 DMX512 external control	1W	42mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ42*73 Hole size: Φ38	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68
	SLGD-BDMD-005 DMX512 external control		52mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ52*84 Hole size: Φ47	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68
	ZZGD-BDMD-007 DMX512 external control	1W	62mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ62*90 Hole size: Φ54	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68
	SLGD-BDMD-009 DMX512 external control	1W	45mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ42*73 Hole size: Φ38	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68
	SLGD-BDMD-011 DMX512 external control	1W	55mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ52*84 Hole size: Φ47	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68
	SLGD-BDMD-013 DMX512 external control	1W	65mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ62*90 Hole size: Φ54	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68

Picture	Item	Power (W)	Description	Input V	Color Temp.	LED Chips	CRI (Ra)	Beam angle	Dimension D*H(mm)	Driver	Light Colour	Material	IP Grade
	SLGD-BDMD-010 DMX512 external control	1W	42mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ42*73 Hole size: Φ38	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68
	SLGD-BDMD-015 DMX512 external control	1W	52mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ52*73 Hole size: Φ47	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68
	SLGD-BDMD-015 DMX512 external control	1W	62mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ62*94 Hole size: Φ54	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68
	SLGD-BDMD-019 DMX512 external control	1W	55mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ55*85 Hole size: Φ48	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68
	SLGD-BDMD-021 DMX512 external control	1W	75mm underground light	DC12/24	3000-6500K	Epistar	≤75	8-60°	Φ75*95 Hole size: Φ65	Constant current driver	White / Y.B.G.R	Stainless Steel #304	IP68