







LED Inground Light

Picture	Item	Power (W)	Input V	Color Temp.	LED Chips	CRI (Ra)	Beam angle	Dimension (mm)	Driver	Light Colour	Material	IP Grade
	SLGD-DMD-001 DMX512 external control	1W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ65*45*70 Hole size: φ45	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65
	SLGD-DMD-002 DMX512 external control	3W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ100*97*80	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65
	SLGD-DMD-003 DMX512 external control	5W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ120*115*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65
	SLGD-DMD-004 DMX512 external control	6W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ120*115*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65
	SLGD-DMD-005 DMX512 external control	9W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ180*160*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65
	SLGD-DMD-006 DMX512 external control	12W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ180*160*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65
	SLGD-DMD-007 DMX512 external control	15W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ200*185*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65
	SLGD-DMD-008 DMX512 external control	18W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ200*185*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65
	SLGD-DMD-009 DMX512 external control	24W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ250*235*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65
	SLGD-DMD-010 DMX512 external control	36W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ300*290*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum- Stainless steel cover	IP65

Picture	Item	Power (W)	Input V	Color Temp.	LED Chips	CRI (Ra)	Beam angle	Dimension (mm)	Driver	Light Colour	Material	IP Grade
	SLGD-DMD-011 DMX512 external control	3W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ100*97*80	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-012 DMX512 external control	5W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ120*115*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-013 DMX512 external control	6W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ120*115*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-014 DMX512 external control	9W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ180*160*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-015 DMX512 external control	12W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ180*160*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-016 DMX512 external control	15W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ200*185*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-017 DMX512 external control	18W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ200*185*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-018 DMX512 external control	24W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ250*235*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-019 DMX512 external control	36W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ300*290*90	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-020 DMX512 external control	3W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ100*100*70 Hole size: 95*95	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-003 DMX512 external control	4W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ120*120*70 Hole size: 110*110	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-004 DMX512 external control	9W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ160*160*90 Hole size: 150*150	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-005 DMX512 external control	12W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ200*200*80 Hole size: 190*190	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-006 DMX512 external control	18W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	φ200*200*80 Hole size: 190*190	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65

Picture	Item	Power (W)	Input V	Color Temp.	LED Chips	CRI (Ra)	Beam angle	Dimension (mm)	Driver	Light Colour	Material	IP Grade
	SLGD-DMD-007 DMX512 external control	24W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	ø250*250*80 Hole size: 240*240	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-008 DMX512 external control	30W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	ø300*300*85 Hole size: 290*290	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-009 DMX512 external control	36W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	ø300*300*85 Hole size: 290*290	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-020 DMX512 external control	5W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	200*80*55 Hole size: 195*75	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-003 DMX512 external control	7W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	300*90*60 Hole size: 285*80	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-004 DMX512 external control	12W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	600*90*75 Hole size: 585*80	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-005 DMX512 external control	18W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	1000*80*75 Hole size: 985*68	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-006 DMX512 external control	24W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	1000*80*75 Hole size: 985*68	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-007 DMX512 external control	36W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	1000*80*75 Hole size: 985*68	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-008 DMX512 external control	36W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	1200*200*85 Hole size: 985*185	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65
	SLGD-DMD-009 DMX512 external control	24W	AC85-265	3000-6500K	Epistar / Macro	≤75	60°	:1200*120*95 Hole size: 1185*100	Constant current driver	White / Y.B.G.R / RGB introcontrol	Die-cast aluminum-Stainless steel cover	IP65