










LED CREE / PHILIPS Track Light

Life Time: 35000Hrs, EPISTAR/CREE Chip + JSIM/GOCOLOR DIM Driver

Picture	Item	Power (W)	Input V	Colour Temp	LED Brand	CRI (Ra)	Beam angle	Dimension D*L(mm)	Hole size (mm)	Driver	Material	Shell Color	Reflector Color	Life Time (h)
	SLBC-ND-01	8/10W	220-240V 110-130V	2700-6400K	CREE Chip	90/93	15° 24° 38°	150*90*130	/	PHILIPS / OSRAM	Alum	Black White	/	50000
	SLBC-ND-06	5/7W	220-240V 110-130V	2700-6400K	CREE Chip	90/93	15° 24° 36°	25*300 40*200	/	PHILIPS / OSRAM	Alum	Black White	/	50000
	SLBC-ND-07	12W	220-240V 110-130V	2700-6400K	CREE Chip	90/93	15° 24° 45°	56*125*152	/	PHILIPS / OSRAM	Alum	Black White	White Black	50000
		18W												
	SLBC-ND-08	25W	220-240V 110-130V	2700-6400K	CREE Chip	90/93	15° 24° 45°	60*178*142	/	PHILIPS / OSRAM	Alum	Black White	White Black	50000
		35W						79*167*189						
	SLBC-ND-20	5/7W	220-240V 110-130V	2700-6400K	CREE Chip	90/93	24°	Φ55*110	/	PHILIPS / OSRAM	Alum	Golden	Golden	50000
		10/12W												

Picture	Item	Power (W)	Input V	Colour Temp	LED Brand	CRI (Ra)	Beam angle	Dimension D*L(mm)	Hole size (mm)	Driver	Material	Shell Color	Reflector Color	Life Time (h)
	SLBC-ND-17	5/7W	220-240V 110-130V	2700-6400K	CREE Chip	90/93	36° 60°	Φ60*110	/	PHILIPS / OSRAM	Alum	Golden	Golden	50000
	SLBC-ND-04	7W	220-240V 110-130V	2700-6400K	CREE Chip	90/93	24° 36°	Φ75*120	/	PHILIPS / OSRAM	Alum	White Black Blue Green Red Yellow Pink	Silver	50000
		10W						Φ85*170						
	SLBC-SD10	8/10W	220-240V 110-130V	2700-6400K	CREE Chip	90 / 93 or 97	15° 24° 36°	Φ50*130	/	PHILIPS / OSRAM	Alum	Black White	Black White	50000
		12/15/18W						Φ65*160						
		20/25/30W						Φ77*185						
	SLSLBC-SD12	8/10W	220-240V 110-130V	2700-6400K	CREE Chip	90 / 93 or 97	15° 24° 36°	Φ65*147	Focus Adjust 3 phase	PHILIPS / OSRAM	Alum	Black White	Black White	50000
		12/15/18W						Φ74*168						
		20/25/30W						Φ95*172						