


Economical LED Flood Light

Picture	Item	Power (W)	Input V	Colour Temp	LED Source	CRI (Ra)	PF	Beam angle	Luminous Efficiency	Size L*H*W(mm)	Driver	Material
	SLTG-A2001/ SLTG-A3001	10W	AC85-265V	3000-6500K	SMD 2835 LED (0.5w/pc) / COB	≥80	>0.6	120°	90-100lm/W	163*132*47	High Power Factor IC Driver	Aluminium
	SLTG-A2002/ SLTG-A3002	20W								212*184*59		
	SLTG-A2003/ SLTG-A3003	30W								241*197*57		
	SLTG-A2004/ SLTG-A3004	50W								286*227*65		
	SLTG-A2005/ SLTG-A3005	70W								280*250*75		
	SLTG-A2006/ SLTG-A3006	100W								326*285*81		
	SLTG-A2007/ SLTG-A3007	150W								400*347*87		
	SLTG-A2008/ SLTG-A3008	200W								405*345*100		

Features

- Energy saving up to 80-90%
- 20-25 times longer life than traditional bulbs
- High quality light
- Extremely low maintenance costs
- No heat, UV or infrared in the beam which helps to protect the eyes
- No mercury
- Instant start
- Safe operation
- Stable performance

Application

1. Tunnel lighting, outdoor lighting, hotel, warehouse, parking lot etc.
2. Billboard, shop sign lighting